

# Long live analog!

Analog tape offers the best chance to create great sounding high-definition masters for digital and vinyl music listening.

When it comes to audio, some aspects of analog technology introduce artifacts and distortions that are perceived as pleasant, and are often musically enhancing and this is something that lies at the heart of the idea of "analog warmth".

Analog audio tapes have been used to record famous albums. The technical limitations and imperfections of analog systems have become an integral part of the quality of the recorded sounds that we all grew up with. Each formulation offers like a painter pallet of different colors, and sound differently.

Musicians, labels, word-class studios still want to be totally engaged by music. They love the sound of analog which adds just the right amount of punch, warmth, fuzziness, rounding off or just plain magic to our drums, vocals, guitar, bass with +9, +6, +3 tapes.

RecordingTheMasters is proud to carry the torch of audio analog recording, and will continue to produce and distribute the tapes for audio engineers who like them for their audio technical and emotional properties, mixing the best albums forever.




Product code	Tape Width		Tape Length		Reel Diameter		Reel Type or Pancake	Hub Type
	Inch	mm	ft	m	Inch	mm		
<b>sm 900</b> RECORDING THE MASTERS	0.25	6,3	600	183	5	130	Plastic Reel	Trident
	0.25	6,3	1 200	366	7	180	Plastic Reel	Trident
	0.25	6,3	2 500	762	10.5	265	Plastic Reel	Trident
	0.25	6,3	2 500	762	10.5	250	Pancake	NAB
	0.25	6,3	2 500	762	10.5	265	Metal Reel	NAB
	0.5	12,7	2 500	762	10.5	265	Metal Reel	NAB
	0.5	12,7	2 500	762	10.5	265	Pancake	NAB
	0.5	12,7	3 750	1 143	12.5	320	Metal Reel	NAB
	1	25,4	2 500	762	10.5	265	Prec. Reel	NAB
	2	50,8	2 500	762	10.5	265	Prec. Reel	NAB
	2	50,8	5 000	1 524	14	360	Prec. Reel	NAB
<b>sm 911</b> RECORDING THE MASTERS	0.25	6,3	600	183	5	130	Plastic Reel	Trident
	0.25	6,3	1 200	366	7	180	Plastic Reel	Trident
	0.25	6,3	2 500	762	10.5	265	Plastic Reel	Trident
	0.25	6,3	2 500	762	10.5	250	Pancake	NAB
	0.25	6,3	2 500	762	10.5	265	Metal Reel	NAB
	0.5	12,7	2 500	762	10.5	265	Metal Reel	NAB
	0.5	12,7	2 500	762	10.5	265	Pancake	NAB
	0.5	12,7	3 750	1 143	12.5	320	Metal Reel	NAB
	1	25,4	2 500	762	10.5	265	Prec. Reel	NAB
	2	50,8	2 500	762	10.5	265	Prec. Reel	NAB
	2	50,8	5 000	1 524	14	360	Prec. Reel	NAB
<b>sm 468</b> RECORDING THE MASTERS	0.25	6,3	600	183	5	130	Plastic Reel	Trident
	0.25	6,3	1 200	366	7	180	Plastic Reel	Trident
	0.25	6,3	2 500	762	10.5	265	Plastic Reel	Trident
	0.25	6,3	2 500	762	10.5	265	Metal Reel	NAB
	0.25	6,3	2 500	762	10.5	265	Pancake	NAB
	0.25	6,3	3 280	1000	10.5	265	Pancake	NAB
	0.5	12,7	2 500	762	10.5	265	Metal Reel	NAB
	0.5	12,7	2 500	762	10.5	265	Pancake	NAB
	1	25,4	2 500	762	10.5	265	Prec. Reel	NAB
	2	50,8	2 500	762	10.5	265	Prec. Reel	NAB
	2	50,8	5 000	1 524	14	360	Prec. Reel	NAB
<b>lpr 90</b> RECORDING THE MASTERS	0.25	6,3	1 800	549	7	180	Plastic Reel	Trident
	0.25	6,3	3 608	1100	10.5	250	Plastic Reel	Trident
	0.25	6,3	3 608	1100	10.5	250	Metal Reel	NAB
	0.25	6,3	3 608	1100	10.5	250	Pancake	NAB
<b>lpr 35</b> RECORDING THE MASTERS	0.25	6,3	885	270	5	130	Plastic Reel	Trident
	0.25	6,3	1 800	549	7	180	Plastic Reel	Trident
	0.25	6,3	3 608	1100	10.5	250	Plastic Reel	Trident
	0.25	6,3	3 608	1100	10.5	250	Metal Reel	NAB
	0.25	6,3	3 608	1100	10.5	250	Pancake	NAB

*Dealer stamp*

Design by Jerome Thom xaxfr

# Professional Analog Audio Tapes





## Pro tapes

**sm<sup>+9\*</sup>**  
**900.**

**PREMIUM HIGH OUTPUT STUDIO TAPE**

- Widths: 1/4", 1/2", 1", 2"
- Backcoated
- Multitrack formats
- Mastering-grade quality
- Low print-through
- Excellent signal-to-noise ratio
- Wide dynamic range

**sm<sup>+6\*</sup>**  
**911.**

**HIGH OUTPUT STUDIO AND ARCHIVE TAPE**

- Widths: 1/4", 1/2", 1", 2"
- Backcoated
- Multitrack formats
- Mastering-grade quality
- Low print-through
- Excellent high-speed winding properties
- Excellent signal-to-noise ratio

**sm<sup>+3\*</sup>**  
**468.**

**STANDARD OUTPUT STUDIO AND ARCHIVE TAPE**

- Widths: 1/4", 1/2", 1", 2"
- Backcoated
- Multitrack formats
- Mastering-grade quality
- Minimal print-through
- Excellent high-speed winding properties
- Allows flangeless operation
- Long-term stability

## Semi-pro tapes

**lpr<sup>+3\*</sup>**  
**90.**

**LONG PLAY VERSION OF SM 900**

- Width: 1/4"
- Backcoated
- Same formulation as SM 900
- Excellent winding properties
- Low-speed recording compatible

**lpr<sup>+3\*</sup>**  
**35.**

**LONG PLAY VERSION OF SM 911**

- Width: 1/4"
- Backcoated
- Same formulation as SM 911
- Excellent winding properties
- Low-speed recording compatible



\* dB over Operating Level (185 nWb/m = 0 VU)



All our tapes are proudly manufactured in France.

## Archiving and Handling Recommendations

For more than 50 years, magnetic tapes have proven themselves to be outstanding as robust, stable carriers of all kinds of information. Nevertheless, problems do occasionally occur during playback. The causes for this usually result from careless handling of the tapes. If handled with cautious care,

magnetic tape is without doubt a long lived archive material. The most important rules can be assigned to three typical areas of application. The climatic conditions should nevertheless be observed in any case. A good climate for a person is also a good climate for a magnetic tape.

Operating and storage climate, upper and lower limits:

	Temperature	Relative Humidity
Studio:	15°C-26°C or 59°F-78°F	45%-70%
Archive:	15°C-22°C or 59°F-72°F	40%-60%

## Magnetic Tape in the Archive

A tape archive should be provided with functioning air conditioning. At the least a thermometer and a hygrometer should be permanently installed in order to have a running check of the climate in the archive. In cleaning the room, no substances should be used that emit acidic components into the air. In regions with heavy industrial air pollution, appropriate air filters must be available. Steel shelves are preferable to wooden ones. Wood shelves store dampness and produces heat energy and harmful gases in the event of a fire.

Tapes that are used for archiving must have even and smooth winding surfaces. Tapes that have been exposed to different operating modes (eg: fast wind then play then fast wind again) exhibit different pressure distribution during winding. To generate equal pressure distribution, it is necessary to rewind the tapes, possibly in "library mode".

In practice, the climatic conditions in a studio and in an archive are not the same. To allow it to acclimatize itself, the tape to be used for archiving

should lie in the archive for several days (protected from dust) before it is packed into a polyethylene bag and placed in an archival holder for final archiving.

Magnetic tapes should basically be stored vertically. Tapes on a hub must be fixed on the hub support.

Audio magnetic tapes should be stored "tail out". This forces a rewind procedure before reuse, whereby the magnetic print-through effect is significantly lessened.

If boxes other than the originals are used, they must be made of acid-free paper, since acids act as catalysts in the decomposition of certain bonding agents.

Temperature cycles cause expansion and contraction of the tape, and lead to uneven pressure distribution in winding and harmful effects on the magnetic layer and base film. In archives with temperature deviations >4°C (>7°F), regular rewinding (every two to three years) is necessary.